



Hood type dishwashers LC700M LC900M LC1200M



LCM



The Blue Line also includes the LC700M, LC900M and LC1200M hood type dishwashers.

These models offer 4 programmes for mid-sized restaurants and other public dining facilities: the first programme is for glasses, the second for plates and cutlery, the third for kitchen utensils, and the fourth, intensive cycle is for the stubbornest dirt.

The electromechanical controls have a selector for choosing the mode of operation: automatic, in which the cycle starts automatically when the hood is closed, or manual, in which the cycle does not start until the start button is pressed.

All kinds of dishware and utensils fit in these units thanks to their 440mm clearance. Upper and lower stainless steel wash and rinse arms with anti

clogging nozzles are standard features.

Easy check of machine operation through light bulbs and maximum hygiene through the thermostop with rinsing starting when 85°C are reached.

The deep drawn tank with rounded corners features four stainless steel filters (optional on mod. LC700M), and an additional filter on the pump suction.

Interlocked booster and tank elements to reduce the installed power. Double wall insulated hood on request.

The CRC option eliminates the need for an exhaust hood. The steam produced inside the machine during the wash cycle is both condensed and cooled down, releasing heat to the incoming water, so that the machine can be connected to cold water with no need for additional kW load.

Highlights

- ✦ AISI 304 stainless steel body with fine matt finish
- ✦ Steam channels on the back
- ✦ Adjustable feet
- ✦ Removable rack holder
- ✦ Pipes outside the washing chamber
- ✦ Manual or automatic cycle start
- ✦ Useful height 440mm
- ✦ Deep-drawn tank with rounded corners
- ✦ Stainless steel upper and lower rotating wash and rinse arms
- ✦ Heaters interlocked
- ✦ Anti-vacuum valve
- ✦ Thermostop
- ✦ Anti noise filter
- ✦ Built-in rinse aid dispenser
- ✦ Prepared for connection with detergent dispenser

Technical info

Model	Glasswashers		Front loaders			Hood type units			
	LB215M	LB275M	LF321M	LF322M	LF700M	LC411M	LC700M	LC900M	LC1200M
	LB215MA	LB275MA	LF321MA	LF322MA	LF700MA				
width (mm)	460	460	600	600	600	632	625	625	625
depth (mm)	520	520	600	600	600	765	760	760	760
height (mm)	635	695	820	820	1260	1460	1460	1460	1460
rack (mm)	400x400	400x400	500x500	500x500	500x500	500x500	500x500	500x500	500x500
washing cycle (sec.)	120	120	120/180	100/150	90/120	120/180	90/120/ 180/480	75/120/ 180/480	55/85/ 120/480
theoretical output* racks/h	30	30	30/20	36/24	40/30	40/30	40/30/20	48/30/20	65/42/30
clearance (mm)	215	275	360**	345**	345**	440	440	440	440
electrical supply	230V 50Hz		230V 50Hz	Multipower	Multipower	Multipower		400V 3N 50Hz	
wash pump (kW)	0,37	0,37	0,45	0,45	0,75	0,75	0,75	1,1	1,5
tank capacity (L)	13	13	21	21	21	22	42	42	42
tank heater (kW)	2	2	2	2	2	2	2	3	3
rinse water consumption (L)	2	2	3,5	3,5	3,5	3,2	3,5	3,5	3,5
booster capacity (L)	6	6	8,2	8,2	8,2	8,2	8,2	8,2	8,2
booster heater (kW)	2,5	2,5	3	5 - 2,5	6 - 3	7	6	8	9
total power (kW)	2,8	2,8	3,45	5,45	6,75	7,75	6,75	9,1	10,5
door switch	yes	yes	yes	yes	yes	yes	yes	yes	yes
built-in water softener	no / yes	no / yes	no / yes	no / yes	no / yes	no	no	no	no
weight (kg)	33 / 37	37 / 41	58 / 62	58 / 62	65 / 69	130	130	135	140
wash arms	PP	PP	PP	sst	sst	sst	sst	sst	sst
drain height (mm)	41	41	55	55	525	560	290	290	290
rinse aid dispenser	yes	yes	yes	yes	yes	yes	yes	yes	yes
detergent dispenser	option	option	option	option	option	option	option	option	option
drain pump	option	option	option	option	option	option	option	option	option
RCD	option	option	option	option	option	option	option	option	option

We reserve the right to modify technical features and pictures.

* In the case of non-stop washing, the cycle duration might be automatically increased to ensure proper rinse temperature.

** clearance for 530x375 trays with special rack.