

GKpv 1470

ProfiLine



Total gross capacity	1427 litre
Ext. dimensions in mm (w/d/h)	1430/830/2150
Int. dimensions in mm (w/d/h)	1240/650/1550
Energy consumption in 24 h	2,315 kWh
Climate rating ¹	T 5
Cooling system	forced-air
Defrosting	automatic
Temperature range	+1°C to +15°C
Gastronorm	530 x 650 mm
Housing material/colour	stainless steel/stainless steel
Door/lid material	Stainless steel
Liner Material	304-grade stainless steel
Type of control	electronic controller
Temperature display	external digital
Interior light	-
Fault: warning signal	visual and audible
Interface	-
volt-free alarm contact	yes
Shelves	9
Adjustable Shelving	8
Number of drawers	-
Number of baskets	-
Maximum number of baskets	-
Shelf material	grid shelves plastic-coated
Shelf loading	60 kg
Height of adjustable legs	120-170
Castors/type of castors	-
Door handle	full-length integrated door handle
Foot pedal opener	-
Self-closing door	yes
Insulation	83 - 60 mm
Defrost water drain	-
Refrigerant	R 290
Noise level	58 dB(A)
Gross/net weight	224/201 kg
EAN-Nr.	9005382170052

¹ Climate Ratings: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C

Subject to modification. Timestamp: 23.03.2015

LIEBHERR