

DONNEES TECHNIQUES TECHNISCHE DATEN DATOS TECNICOS



CM1519(A)	CM1529(A)	CM1919(A)	CM1929(A)
Manual Controls Commandes manuelles Manuelle Kontrollen Mandos Manuales	Programmable Controls Commandes programmables Programmierbare Kontrollen Mandos Programables	Manual Controls Commandes manuelles Manuelle Kontrollen Mandos Manuales	Programmable Controls Commandes programmables Programmierbare Kontrollen Mandos Programables
26 (0.9) litres (cu.ft)	26 (0.9) litres (cu.ft)	26 (0.9) litres (cu.ft)	26 (0.9) litres (cu.ft)
1500 Watts	1500 Watts	1850 Watts	1850 Watts
High – 1500 Watts Medium – 1050 Watts Low – 750 Watts Defrost 1 – 375 Watts Defrost 2 – 195 Watts	High – 1500 Watts Medium – 1050 Watts Low – 750 Watts Defrost 1 – 375 Watts Defrost 2 – 195 Watts	High – 1850 Watts Medium – 1295 Watts Low – 925 Watts Defrost 1 – 370 Watts Defrost 2 – 185 Watts	High – 1850 Watts Medium – 1295 Watts Low – 925 Watts Defrost 1 – 370 Watts Defrost 2 – 185 Watts
13 amp	13 amp	13 amp	13 amp
230/50 V/MHz	230/50 V/MHz	230/50 V/MHz	230/50 V/MHz
2,430 MHz	2,430 MHz	2,430 MHz	2,430 MHz
32 kg	32 kg	32 kg	32 kg
-	30	-	30
368x464x557 (40*) HxWxD (mm)	368x464x557 (40*) HxWxD (mm)	368x464x557 (40*) HxWxD (mm)	368x464x557 (40*) HxWxD (mm)
190x370x370 HxWxD (mm)	190x370x370 HxWxD (mm)	190x370x370 HxWxD (mm)	190x370x370 HxWxD (mm)